



RAEGuard 2 PID

Fixed photoionisation detector
(PID)

REDUCED MAINTENANCE COSTS

- Easy to remove sensor module in hazardous locations without use of tools

REDUCED LIFE COSTS

- Unique lamp design makes the product more robust and enables longer life time

AVAILABILITY

- Continuous VOC monitoring in hazardous and non-hazardous locations

PROVIDES FASTER RESPONSE TIMES

- The sample flow-through design powered by an internal diaphragm pump provides faster response times

ACCURATE READINGS

- Guaranteed by humidity compensation even in humid environments

ADVANCED TECHNOLOGY

- Patented pump duty cycle extending the sensor and lamp cleaning interval
- Patented Electronic zero keeping the zero point stable
- Patented 3D sensor technology lower quenching effect - faster response to high concentration - lower RH response

SUITABLE FOR A WIDE RANGE OF APPLICATIONS

- Over 200 correction factors¹ are pre-programmed and allow users to display readings of specific target gas

KEY APPLICATIONS AND THEIR VOCS

- Benzene in refinery analyser shelters
- Ammonia in industry
- Vinyl Chloride in chemical manufacturing
- Toluene or Ammonia in semi-conductor plants
- Solvent and chemicals storage
- Phenol and DME in pharmaceutical
- Toluene in printing
- Air quality
- Methyl Ethyl Ketone in paint spray booths
- Heat transfer fluids
- Acetone, Xylene, Phenol in medical, pathology, histology lab

Status at a glance

The RAEGuard 2 PID operates on 10 to 28 VDC and provides an analogue (4-20mA) three-wire signal output, and RS-485 Modbus digital signal output.

Calibration has been greatly simplified with the introduction of Electronic Auto-zero patented by Honeywell.

The RAEGuard 2 PID is utilizing many of Honeywell's PID patents such as the electronic Auto-zero that guarantees an incomparable base line stability making it the best in class product.

Polynomial based calibration provides superior calibration linearity throughout the full range.

The RAEGuard 2 PID has a graphic display and LED light status indicator for fault and alarm conditions. In addition, low, high, and fault relays* can be configured to trigger external alarms or process controls.

A magnetic key interface enables the detector to be calibrated and operational parameters adjusted with the explosion-proof enclosure in place.


¹Relays and Correction factors are disabled when using the 1 to 1000 ppm DigiPID



Technical Specifications



RAEGuard 2 Fixed Sensor Head



DigiPID Sensor Module

RAEGUARD 2 FIXED SENSOR HEAD SPECIFICATIONS

BASIC PARAMETERS	
WORKING CURRENT	DC 10 to 28V, 210mA at 24V
POWER	<5W
OUTPUT	4-20mA Three-level programmable alarm relays (30 VDC, 2A) RS-485 (Supports Modbus)
SAMPLING	Internal diaphragm pump, up to 500cc/min
IP RATING	IP-65
MECHANICAL INTERFACE	3/4" NPT Male
INSTALLATION	50.8 mm (2") pipe-holding or wall mounting
USER INTERFACE	Three-key magnetic bar adjustment
CALIBRATION	Two points
WARRANTY	1 year for the pump, 2 years for the housing and electronics
ENVIRONMENTAL PARAMETERS	
TEMPERATURE	-20°C to +55°C (-4°F to 131°F)
HUMIDITY	0 to 95% relative humidity, non-condensing
PRESSURE	90 to 110kPa
DISPLAY	
DISPLAY	128 x 64 matrix backlit LCD, supports graphic display
128 X 64 MATRIX BACKLIT LCD, SUPPORTS GRAPHIC DISPLAY	
SIZE	10.1" L x 7.9" W x 4.2"H (257 x 201 x 107 mm)
WEIGHT	3.5 kg (7.7 lbs)
MATERIAL	316 stainless steel
CERTIFICATION	
ATEX	Ex II 2(1)G, Ex d [ia Ga] IIC T4 Gb
UL/CSA	Class 1, Div. 1, Groups ABCD T4
IECEX	Ex d [ia Ga] IIC T4, Gb
TR CU	1Ex d [ia Ga] IIC T4 Gb X

DIGIPID SENSOR MODULE SPECIFICATIONS

POWER SUPPLY	5V ±0.25V DC
CURRENT	110mA max
POWER CONSUMPTION	< 0.6W
MEASURING RANGE	0.01 to 100 ppm 0.1 to 1000 ppm 1 to 1000 ppm (No relays or correction factors)
RESOLUTION	10 ppb, 1 ppm (depends on model)
RESPONSE TIME	Pumped (T90): <30 s
CALIBRATION	Two-point off-line and field calibration Optional three-point calibration
ACCURACY	±2% for calibration point
ANALOGUE OUTPUT	0.5 - 2.5V (ro=1.0k)
DIGITAL INTERFACE	Serial Interface (UART) Transmit (Tx): 3.3V TTL Receive (Rx): 3.3V TTL
WARRANTY	2 years for the lamp, 1 year for the sensor, electronics and housing
OPERATING TEMPERATURE	-20°C to +55°C (-4°F to +131°F)
HUMIDITY	0 to 95% RH non-condensing
EMI/RFI	Highly resistant to EMI/RFI compliant with EMC directive 2004/108/EC
PACKAGE	316 stainless steel Spray watertight for IP-65 rating Dust membrane for sensor front protection
SIZE	49 mm x 150.8 mm (1.92" D x 5.94" L)
WEIGHT	< 550g (19.4 oz)
CERTIFICATION	
ATEX	II 1 G EX ia IIC T4 and 1M1 Ex ia I
UL/CSA	Class I, Div. 1, Groups A B C D T4
IECEX	Ex ia IIC T4 Ga and Ex ia I
TR CU	0Ex ia IIC T4 Ga X

RAEGUARD ORDERING OPTIONS

RAEGUARD 2 FIXED SENSOR HEAD INCLUDES	<ul style="list-style-type: none"> Explosion-proof stainless steel enclosure with LCD display, integrated sampling pump and relays, digital connector for external sensors Magnetic key
DIGIPID SENSOR MODULE INCLUDES	<ul style="list-style-type: none"> Complete stainless steel PID sensor module with UV lamp and digital connector output for use with RAEGuard 2 Choice of detection range 0.01 to 100 ppm, 0.1 to 1000 ppm or 1 to 1000 ppm DigiPID maintenance kit
RAEGUARD 2 PID KITS INCLUDES	<ul style="list-style-type: none"> All RAEGuard 2 Fixed Sensor Head contents and all DigiPID contents as stated above



Honeywell Gas Detection

Honeywell is able to provide gas detection solutions to meet the requirements of all applications and industries. Contact us in the following ways:

Find out more:

www.honeywellanalytics.com
www.raesystems.com

Europe, Middle East, Africa

Life Safety Distribution GmbH
Javastrasse 2
8604 Hegnau
Switzerland
Tel: +41 (0)44 943 4300
Fax: +41 (0)44 943 4398
gasdetection@honeywell.com

Customer Service:

Tel: 00800 333 222 44
(Freephone number)
Tel: +41 44 943 4380
(Alternative number)
Fax: 00800 333 222 55
Middle East Tel: +971 4 450
5800 (Fixed Gas Detection)
Middle East Tel: +971 4 450
5852 (Portable Gas Detection)

www.honeywell.com

Americas

Honeywell Analytics Distribution Inc.
405 Barclay Blvd.
Lincolnshire, IL 60069
USA
Tel: +1 847 955 8200
Toll free: +1 800 538 0363
Fax: +1 847 955 8210
detctgas@honeywell.com

Honeywell RAE Systems
Phone: 408.952.8200
Toll Free: 1.888.723.4800
Fax: 408.952.8480

Datasheet_RAEGuard2PID_DS01144_V5_07-17_EMEA | 07/17
© 2017 Honeywell International Inc.
All rights reserved.

Asia Pacific

Honeywell Industrial Safety
7F SangAm IT Tower,
434, Worldcupbuk-ro, Mapo-gu,
Seoul 03922,
Korea
Tel: +82 (0) 2 6909 0300
Fax: +82 (0) 2 2025 0328
India Tel: +91 124 4752700
China Tel: +86 10 5885 8788 3000
analytics.ap@honeywell.com

Technical Services:

EMEA: HAexpert@honeywell.com
US: ha.us.service@honeywell.com
AP: ha.ap.service@honeywell.com

While every effort has been made to ensure accuracy in this publication, no responsibility can be accepted for errors or omissions. Data may change, as well as legislation, and you are strongly advised to obtain copies of the most recently issued regulations, standards, and guidelines. This publication is not intended to form the basis of a contract.

Honeywell